TRI STAR WITH STALK, 12V 316 STAINLESS STEEL HOUSING, LOC-LINE™
















Machined Exclusive





ITEM	Α	В	С	COLOR	X (height)	Y (length)	Z (width)	WT (lb)	PACKAGING TYPE	EACH (qty)	INNER (qty)	CARTON (qty)	UPC
S0803-1040	0.40"	0.50"	3.56"	WHITE	0.72"	6.02"	0.72"	0.12	POLYBAG	1	10	300	791506052883
S0803-104R	0.40"	0.50"	3.56"	RED	0.72"	6.02"	0.72"	0.12	POLYBAG	1	5	375	791506052890
S0803-1080	0.40"	0.50"	6.20"	WHITE	0.72"	10.13"	0.72"	0.13	POLYBAG	1	10	250	791506052906
S0803-108R	0.40"	0.50"	6.20"	RED	0.72"	10.13"	0.72"	0.13	POLYBAG	1	10	350	791506052913
S0803-1120	0.40"	0.50"	8.00"	WHITE	0.72"	14.00"	0.72"	0.16	POLYBAG	1	5	200	791506052920
S0803-112R	0.40"	0.50"	8.00"	RED	0.72"	14.00"	0.72"	0.16	POLYBAG	1	10	250	791506052937

NOTE:

TRI STAR IS ATTACHED TO FLEXIBLE STALK. MOST EFFICIENT IN POWER CONSUMPTION 20 MA @13 VDC (TYPICAL), PLUS THE ADDITION OF DIRECTING LIGHT WHERE NEEDED. IDEAL FOR CHART TABLES, AS A WORKLIGHT ON MACHINES AND IN LANDSCAPE OR ARCHITECTURAL APPLICATIONS. ALL DIMENSIONS ARE NOMINAL (+/- 3%) AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.